

# WALKER GOSSAN PROJECT

Northern Territory, Australia. EL 24305 - Nov. 2016

SELECTED DRILL HOLE ASSAY INTERVALS					
hole	interval				depth
WD -01	9.5m	@	4587 ppm Pb	from	35.5m
WD -02	32.5m	@	1786 ppm Pb	from	0.0 m
WD -04	18.5m	@	2264 ppm Pb	from	3 m
WD - 02	4 m	@	414 ppm Zn	from	29m
WD -04	4.5m	@	375 ppm Zn	from	0.0m
WD -01	9.0m	@	588 ppm Cu	from	33m
WD -04	8.5m	@	310 ppm Cu	from	92m
WD- 01	2.5m	@	15.1 ppm Ag	from	39.5m
WD -04	0.5m	@	28.5 ppm Ag	from	99.5m

# WALKER GOSSAN PROJECT

ELA 24305 - Nov. 2016 - WD#1

HOLE	DEPTH	INTERVAL	ASSAY PPM
<b>WD#1</b>			
<b>Pb &gt;500ppm</b>	<b>33m-34.5m</b>	<b>1.5</b>	<b>1668.7</b>
	<b>35.5m- 45m</b>	<b>9.5</b>	<b>4587.7</b>
<b>Cu &gt;100ppm</b>	<b>33m-34.5m</b>	<b>1.5</b>	<b>162.7</b>
	<b>33m- 42m</b>	<b>9.0</b>	<b>588.8</b>
<b>Ag &gt;10ppm</b>	<b>39.5 - 42</b>	<b>2.5</b>	<b>15.1</b>

# WALKER GOSSAN PROJECT

ELA 24305 - Nov. 2016 - WD#2

HOLE	DEPTH	INTERVAL	ASSAY PPM
<b>WD#2</b>			
<b>Pb &gt;500ppm</b>	<b>0-32.5</b>	<b>32.5</b>	<b>1786.1</b>
<b>Zn &gt;100ppm</b>	<b>2-4m</b>	<b>2.0</b>	<b>119.8</b>
	<b>29-34.5</b>	<b>6.5</b>	<b>367.1</b>
<b>Cu &gt;100</b>	<b>0- 6.5</b>	<b>6.5</b>	<b>228.8</b>
	<b>17-18</b>	<b>1.0</b>	<b>242.0</b>
	<b>24.5-25.5</b>	<b>1.0</b>	<b>201.0</b>
	<b>27.5-28.5</b>	<b>1.0</b>	<b>394.0</b>
	<b>29-33</b>	<b>4.0</b>	<b>779.0</b>

# WALKER GOSSAN PROJECT

ELA 24305 - Nov. 2016 - WD#3 and WD#6

HOLE	DEPTH	INTERVAL	ASSAY PPM
------	-------	----------	-----------

WD#3			
Pb >500ppm	0-1	1.0	521.5
	3- 12.5	9.5	2645.0
	5.5- 8.5	3.0	734.7
	23-29	6.0	236.6
Ag >10	25-26	1.0	14.8

WD#6			
Pb >500ppm	2.0 - 10.0	8.0	1386.8
Cu >100ppm	3.5-4.5	1.0	208.0
	12.5-17.5	5.0	296.5
	56-57	1.0	128.5

# WALKER GOSSAN PROJECT

ELA 24305 - Nov. 2016 - WD#4

HOLE	DEPTH	INTERVAL	ASSAY PPM
WD#4			
Pb >500ppm	0-1	1.0	7725.0
	3-24.5m	21.5	2580.2
Zn >100ppm	0 -4.5m	4.5	375.2
	15.5-16.5	1.0	229.0
	20-24.5	4.5	282.0
Cu >100ppm	0-1	1.0	301.0
	15.5-18.5	3.0	148.2
	21.5-24.5	3.0	232.0
	24.5-27	2.5	173.4
	30.5-32.5	2.0	185.3
	92-100.5	8.5	310.6
Ag >10ppm	0-1	1.0	11.1
	3 to 6	3.0	15.3
	15.5- 18	2.5	12.6
	99.5-100	0.5	28.5